



## **B1-**220ASC

Superior in design and in performance, the B1 Series incorporates a wide range of features designed for University and Laboratory use. Superb optical clarity and reliable mechanical engineering assure years of top performance.

Model	B1-220ASC
Optical System	Finite Optical System, 160mm
Observation tube	Binocular, sliding type
Interpupillary distance	55-75mm
Inclination	45° inclined, 360° rotating
Eyepiece(s)	WF10X/20mm
Nosepiece	Quadruple revolving nosepiece with click stops
<b>Objective classification</b>	ASC Achromatic Super Contrast, DIN
<b>Objective information</b>	4X/0.10 (WD 17mm), 10X/0.25 (WD 6.4mm),
	40X/0.65/S (WD 0.45mm), 100X/1.25/S-Oil (WD 0.14mm)
Objective mounting thread	W 4/5" x 1/36" (RMS standard)
Stage	Built-in low position coaxial mechnical stage with sample holder
Stage size	140X135mm
Mechanical stage X&Y range	78X50mm
Upper limit stop	Upper limit stop preset but adjustable
Condenser	Rack & pinion focusable 1.25 N.A. Abbe Condenser, with iris diaphragm and filter holder
Free Working Distance	Coaxial coarse and fine focusing system with tension adjustment
Fine Focus precision	2 µm minimum increment
Z-axis movement	27mm
Filter holder	12V/20W Halogen illumination with intensity control
Transformer	Internal
Power supply	220-240V (CE)
Accessories included	Blue, yellow and green filters, dust cover and immersion oil
Lenght X Width X Height	245X190X380
Weight KG	6,8KG



Add a Moticam camera to capture, document, annotate and share images and videos with the Motic Images Plus 2.0 software.