



Motic combines CCIS optics with innovative mechanical design, unrivalled versatility, ergonomics and optical excellence and brings you a new series of inverted microscopes.



THE MOTIC AE30/31 SERIES PROVIDES YOU WITH EXCELLENT OPTICAL QUALITY AND UNMATCHED OPERATIONAL CONVENIENCE

COLOUR CORRECTED INFINITY OPTICAL SYSTEM

The CCIS optics allows new accessories and functions to be incorporated into the AE30/31 inverted microscope.

The CCIS infinity design has succeeded in achieving longer working distance objectives with higher numerical apertures. This represents a significant development in optical performance and versatility.



THE MICROSCOPE STAND

The design of the AE30/31 inverted microscopes optimally integrates all functions enabling effective ergonomics and maximum expandability.

The wide base provides strength and rigidity. In addition, the inverted "Y" support in the back of the microscope provides extra lateral stability.

The AE30/31 has been designed to meet the needs of demanding users. The size of the microscope is compact to minimize the footprint and conserve limited desk space available in modern laboratories.

The ergonomic design has made AE30/31 compatible with the manner in which you work. The coaxial coarse/fine focusing knobs, controls for the attachable mechanical stage and light intensity, are placed conveniently at your fingertips to minimize user fatigue. The ideally positioned focus knobs and stage controls make their manipulation stress free.



THE LIGHT SOURCE

The Koehler illumination system with a 6V-30W Quartz halogen lamp provides bright, even illumination at any magnification. The "only one in its class" centerable lamp is housed externally and has an externally operated mechanism for control of all facets of illumination. A segmented illumination intensity indicator is ideally located for easy viewing.





THE REVOLVING NOSEPIECE

The revolving side facing nosepiece accepts five objectives. It runs on ball bearings and has internal click stops so that the image remains centered after each change in magnification.





SPILL RESISTANT DESIGN

Internal components and optics are sealed against accidental fluid spills. This allows the user to concentrate fully on the specimen and not to worry about accidentally damaging the microscope.

The Motic AE30/31 ensures reliable and trouble-free usage.





OBSERVATION TUBES

In order to maintain parfocality, the AE30/31 Siedentopf eyepiece tubes will not change their length when interpupillary distance adjustments are made. An inclination angle of 45° is chosen for comfort and posture management.



STAGE AND ACCESSORIES

The standard stage is a fixed stage plate. The stage can be widened on both sides with auxiliary stage plates. A hard coating protects the stage surface from abrasion and wear. The tempered glass stage insert allows for checking the objective being used without removing the specimen from the stage.

An optional attachable mechanical stage with low positioned coaxial controls is available. The controls are ergonomically positioned so that your hands can rest on the desk while scanning the specimen.

The object guide accepts interchangeable specimen holders: 65mm Petri dish holder (optional 35mm Petri dish holder), 54mm Petri dish holder, standard glass slides.



EYEPIECES

A field of view of 22mm has now been adopted as the standard for 10X eyepieces. This enlarged field provides for faster scanning and easier viewing.

Parfocality of focus is assured by independent diopter adjustment provided on each eyepiece.

Various graticules for measurement and counting can be used with the adjustable eyepieces.







CONDENSER MOUNT

The centerable condenser mount is height adjustable with rack and pinion and is dovetail mounted on an illuminating pillar with a clamp screw.

The ELWD condenser with a numerical aperture of 0.30 and a working distance of 72mm is suitable for objectives of magnification from 4X to 40X with an aperture diaphragm in the brightfield Koehler illumination and for phase contrast.

For easy and quick change of magnification, two annular rings on a standard non-centerable phase slider (to be released) and a centerable version, recommended for more demanding examinations, are available.

The phase annular ring Ph1 for 10X and 20X and Ph3 for 40X are centered by Allen Hex keys on the centerable slider. The center position on each slider is designated for brightfield usage.







OBJECTIVES

The Motic CCIS objectives for inverted microscopes have long free working distances in comparison to normal objectives of the same magnification. The objectives are optically corrected to compensate for different base thickness of specimen holders and provide easy routine operation.

These objectives also make it possible to turn the objective nosepiece, even at the highest magnifications, without fear of coming into contact with the object stage.

Choices of objectives:

Description	Туре	N.A.	W.D. (mm)	Phase Ring	
Achromat Plan	PL 4X ∞	0.1	23.5	-	
	PL 10X ∞	0.25	7.5	-	
	LWD PL 20X ∞	0.4	7	-	
	LWD PL 40X ∞	0.6	2.8	-	
Phase Plan	PL Ph 10X ∞	0.25	7.5	Ph1	
Achromat	LWD PL Ph 20X ∞	0.4	7	Ph1	
	LWD PL Ph 40X ∞	0.6	2.8	Ph3	

The newly designed 20X and 40X brightfield objectives and 20X and 40X phase objectives, which compensate for a 1.1mm thick cover glass, require no cover glass compensation and provide routine operation.



PHASE CONTRAST MICROSCOPY

Phase contrast is the most popular optical contrast method for viewing the detailed structure of unstained or living specimens.

The Motic Phase Plan Achromat objectives, coupled with the easy to operate phase slider, provide outstanding contrast for the most demanding application.

For a quick and easy change of magnification, two annular rings are provided on the non-centered phase slider. The center position on the slider is designated for brightfield microscopy (to be released).

The annular rings on the centerable phase slider are centered with the provided Allen Hex keys.

DIMENSIONS INFORMATION



SPECIFICATIONS

Illumination

Condenser

Collector

6V-30W Quartz halogen centerable lamp is housed

externally and has an externally operated device for

all the elements of illumination with built-in heat

absorbing filter and removable diffuser

ELWD N.A. 0.30 (W.D. 72mm) Focusable

LWD N.A. 0.50 (W.D. 28mm) Focusable

Aspherical lens with field diaphragm

for objectives 4X to 40X

			1					_
	AE-30	AE-31		Specifications		Order No.	AE30	AE31
Optical system	CCIS (Colour corrected infinity optical system). Parfocal distance: 45mm		Eyepieces	Widefield High Eyepoint	WF PL 10X/22 with diopter adjustment	SG02S0144	I	I
			CCIS Infinity	LWD Phase	CCIS PL Ph10X	SG01S02291	1	1
Observation	Siedentopf type	Siedentopf type	Objectives		CCIS LWD PL Ph20X	SG01S03291	1	1
tubes - - -	binocular tube	trinocular tube			CCIS LWD PL Ph40X	SG01S04291	D	D
		(light distribution,		LWD Plan	CCIS PL4X	SG01S01241	I	1
		bino/photo:100/0			CCIS PL10X	SG01S02241	1	I
		or 0/100)			CCIS LWD PL20X	SG01S03241	1	I
	Inclination				CCIS LWD PL40X	SG01S04241	I	I
	15.1	15			CCIS LWD PL60X	SG01S05241	I	I
	45 degrees 45 degrees		Condenser	ELWD N.A. 0.30 (W.D. 72mm)		SG030401A	I	I
				LWD N.A. 0.5 (W.D. 28mm)		SG030701	1	I
	50-75mm	50-75mm	Phase Slider	Centerable: Ph1, Ph	n3, One empty position	SW0123F8	۱*	*
	Eyepoint height			Non-centerable - Ph1, Brightfield, Ph3 (to be released)				
	380mm from table	400mm from table	Phase Contrast	Phase Centering Telescope (Ø30)		SG069993	*	*
Eyepieces	Widefield High Eyepoint WF PL10X (FN 22)		Accessories					
	with diopter adjustment		Photo Adapters	Photo Adapter (requires one of the photo eyepieces below) 2.5X Photo eyepiece		SP100294		I
Nosepiece	Quintuple nosepiece, side fa	Quintuple nosepiece, side facing type				SG02S1001		1
Plain stage	Stage size: 200 x 260mm.]	4X Photo eyepiece		SG02S1101	/	I
	Stage height: 207mm from table.		Video Adapters	s CCD adapter 0.65X		SP100384	1	I
Focusing	Coaxial / via nosepiece up / down movement		11	CCD adapter 1X		SP100350	/	I
	Coarse / fine movement - 42mm / 0.2mm		Stage &	Glass stage insert		SP100301	I	I
	Min. fine meeting 2 um Adjustehle soorse terrus		Accessories	Metal stage insert		SW0199F9	I	I
	Min. fine reading 2µm. Adjustable coarse torque		Auxiliany stages (ps		ired set)	SW/0123G3	1	1

Notes: " I " represents the standard accessories. " I " represents the optional accessories.

I

L

Т

L

T.

L

L

۱*

Ī.

L.

I.

I.

I

L

L.

۱*

SW010392

SP100303

SP100304

SP100302

SG060747

SG060727

SG060729A

SP070014

STANDARD & OPTIONAL SET CONFIGURATION

" to be used with phase objectives.

Allen Hex. Key Two keys provided

Filters

" ID represents the optional accessories for some markets.

Universal attachable mechanical stage

Green interference (45mm diameter)

with well plate holders

35mm Petri dish holder

54mm Petri dish holder

65mm Petri dish holder

Blue filter (45mm diameter)

Ground glass (45mm diameter)

Please check with your local Motic Agent.





Note: " ** " to be used with phase objectives





URL: http://www.motic.com Motic Incorporation Ltd. (HONG KONG) Rm. 2907-8, Windsor House, 311 Gloucester Road, Causeway Bay, Hong Kong Tel: 852-2837 0888

 Motic Instruments Inc. (CANADA)

 180-4320 Viking Way Richmond, B.C. V6V 2L4 Canada

 Tel: (604) 303-9033 Fax: (604) 303-9043 Toll Free: 1-877-977-4717

 Technical Support: 1-877-901-4141 Email: info@motic-america.com

For inquiries in UK (UK) Saracens House, 25 St. Margarets Green, Ipswich, IP4 2BN, Suffolk, UK Tel: 44-(0)-14732 81909

Motic Deutschland GmbH (GERMANY) Gewerbepark Spilburg, Gebäude A42 Spilburgstrasse 1 D-35578 Wetzlar Germany Tel: 49-6441-210 010

Motic Spain, S.L. (SPAIN) C/Pere IV, 78-84-7 Planta 08005 Barcelona Spain Tel: 34-93-485 1841

Motic China Group Co., Ltd. Copyright @ 2002-2004. All Rights Reserved

Design Change: The manufacturer reserves the right to make changes in instrument design in accordance with scientific and mechanical progress, without notice and without obligation.



Code: SP010686EB